

DV-HVR7032DM
2 SATA 5 in one DVR



Features :

- Support 32ch 1080Nunreal-time encoding;
- Support AHD, TVI, CVI,CVBS, IP video input;
- HDMI/VGA simultaneous video output;
- BIG 1U Case, 2 SATA(Up to 8TB);
- 1*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;

Model :

DV-HVR7032DM

Interface :



Parameters :

| | Model | DV-HVR7032DM | |
|------------|---------------|--|---|
| System | processor | Hi3531A | |
| Video | Codec | H.264 | |
| | preview | 32*1080N (5 in 1) | |
| | Encode | 32*1080N@15fps (5 in 1) ; | |
| | Decode | 8*1080N@15fps (5 in 1) ; | |
| | Multi-mode | | Analog:32*1080N@15fps (5 in 1) |
| | | | Hybird:8*1080N(analog)+8*960P(network) IP:32*1080P;16*3M ;8*5M |
| | Playback | 8ch | |
| Audio | Compression | G.711a | |
| | Intercom | Support | |
| Management | Record mode | Manual>Alarm>Motiondetection>Timing | |
| | Inquire mode | Inquire by Time/Calendar/Event/Channel | |
| | Storagemode | HDD Storage, Network Storage | |
| | Backup | Network, USB, SATA | |
| Interface | Video input | 32*BNC (Support Coaxitron) | |
| | HDMI output | 1*HDMI (MAX:1080P) | |
| | VGA output | 1*VGA (MAX:1080P) | |
| | Audio I/O | 16/1 | |
| | Alarm I/O | 8/1 | |
| | Ethernet port | 1*10/100/1000Mbps Ethernet port, RJ45 port | |
| | PTZ control | 1*RS485,1 ↑ RS232 ;Support for multiple PTZ protocol | |
| | USB Port | 2*USB2.0 ports | |
| | HDD | 2*SATA interface (Up to 8TB) | |
| General | Temperature | 0 °C - + 55 °C | |
| | Humidity | 10% -90% RH | |
| | Power supply | 12V/4A | |
| | Consumption | <10W (Without HDD) | |
| | Weight | Around 3KG | |
| | Dimension | 440mm(L)* 290mm(W)* 50mm(H) | |